

# UNIVERGE® SV9100 COMMUNICATION SERVER



## Smart Communications for **Small and Medium Businesses**

The **UNIVERGE® SV9100 Communications Server** is a robust, feature-rich and scalable system that is ideal for small and medium businesses. It is designed to help solve today's communications challenges and offers the ability to expand as your business grows in the future.

The SV9100 offers:

- > **Multi-carrier SIP support** – Offers greater resilience and provides more cost effective routing of calls
- > **VoIP and Traditional Voice Support** – Deploy a pure IP solution or any combination of IP and traditional circuit-switched technology with a single SV9100 system
- > **Application Integration** – Embedded applications are easily accessed through simple license activation
- > **Scalability** – As a business's communication needs grow with the company
- > **Stackable Architecture** – The SV9100's rack stackable chassis supports server functions, media gateways and media converters through a single unit



### Easy migration from the SV8100

- > Investment protection
- > More features and improved functionality
- > Enhanced Unified Communications (UC) choices
- > High capacity - almost double the ports of the SV8100

# NEC UNIVERGE® SV9100 Communication Server



## Technical Data

Chassis	9.5"			19"		
Number of SV9100s	1	1	2	3	4	w/ NetLink
Outside Lines	<b>IP Lines</b>					
	• IP Trunks (SIP)*			400**		
	<b>Analogue Trunks</b>					
	• Analogue Trunks (COT)	16	40	88	136	184
Terminals	• PRI Channels					
	• BRI Channels					
	<b>IP Terminals</b>					
	• UNIVERGE DT800 Series					
• SP310 Soft Phone						
• SIP DECT terminals						
<b>Digital terminals (TDM)</b>						
• UNIVERGE DT400 Series						
<b>Analogue terminals</b>						
• SLT (-24V)						
• SLT (-48V)						
Applications**	• IP Gateway channels					
	• IP Gateway channels with sRTP					
	<b>Embedded Applications</b>					
	<i>Voicemail</i>					
	• VM InMail					
	• VRS channels					
	<i>InACD</i>					
	<b>In-Skin Applications</b>					
	• Gigabit POE switch					
	<b>Networking</b>					
	• NetLink networking #					
	• FeatureNet (AspireNet)					
	• K-CCIS networking					
	Physical characteristics	• SV9100 chassis dimensions			88 x 430 x	
115 x 220 x 369 mm (hxwxd)			390 mm (hxwxd)			
Power consumption	• Empty chassis weight			896 Mailboxes (896 subscribers, 32 groups, 32 call routing mailboxes)		
	2.15 Kg			6.35 Kg; Average weight of cards 275 g (maximum 6 cards in chassis)		
Compliance	• SV9100 Chassis Power Rating					
	Input 100V/120V/220V/230-240V - 2.43A/2.19A/1.19A/1.15A 50/60Hz					
The SV9100 Communications Server carries a CE mark and complies with:						
• EMC						
• Safety						
• Transmission and signalling						

\* Maximum number of simultaneous calls is limited by the Voice over IP Resources (IP Pad Channels) available

\*\*Maximum number based on peer to peer, maximum independent of chassis configuration

For further information please contact NEC EMEA or:

EMEA (Europe, Middle East, Africa)  
NEC Enterprise Solutions  
www.nec-enterprise.com